

INSPECTION FORM: FULL BODY HARNESS



OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

WHAT IS THE FREQUENCY OF INSPECTION IN THE FOLLOWING CATEGORIES?

General Industry: _____

Construction: _____

Your Organization: _____

Manufacturer: _____

MANUFACTURER OF EQUIPMENT: _____

NAME OF COMPETENT PERSON: _____

NAME OF USER (AUTHORIZED PERSON): _____

DATE OF INSPECTION: _____ REMOVE FROM SERVICE WHEN? _____

Date: ___/___/___ Date: ___/___/___

LOOK AT:

- 1** Hardware **2** Webbing
- 3** Stitching **4** Labels / Tags

LOOK FOR:

1 HARDWARE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Rust/corrosion		
Deformed/bent		
Burs/cracks		
Weld spots/slag		
Missing rivets		
Springs		
Functionality		
Other		

2 WEBBING	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cuts/burns/holes		
Excessive wear		
Excessive UV damage		
Chemical attack		
Writing on the webbing		
Other		

3 STITCHING	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Missing		
Loose		
Broken		
Other		

4 LABELS / TAGS	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Missing		
Illegible		
Dates		
Other		

